



◆ SPECIFICATION

Model NO.	NDA5W12	
Video Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps
Camera		
Image Sensor	1/3" CMOS Sensor	1/2.5" CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080
Electronic Shutter	AUTO	AUTO
TV System	PAL/NTSC	PAL/NTSC
Scanning System	Progressive Scan	Progressive Scan
Lens		
Focus Length	Board Lens 2.8-12mm	Board Lens 2.8-12mm
Focus Control	Manual	Manual
Lens Type	Manual	Manual
Night Vision		
IR Cut Filter	YES	YES
Infrared LED	14μ x 24PCS	14μ x 24PCS
Infrared Distance	30M	30M
IR Status	AGC Auto Control	AGC Auto Control
Camera Features		
Starlight	/	/
Day/Night	YES	YES
OSD Menu Language	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO
Noise Reduction	DNR	DNR
WDR	DWDR	DWDR
UTC	YES	YES
General		
Housing	IP67	IP67
Bracket	NO	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,750mA	DC12V±10%,750mA
Dimension	∅ 119 x 98(H) mm	∅ 119 x 98(H) mm
Weight	800g	800g