

NEOVISION



SPECIFICATION

Model		ND32CN5
System		
Main Processor	HI3531D	
Operating System	Embedded LINUX	
Video		
Input	Normal Mode: Analog: 32*(AHD/TVI/CVI:8M; TVI/AHD: 5M; AHD/TVI/CVI: 4M; AHD/TVI: 3M; AHD/TVI/CVI: 1080P/720P; Analog: 960H) Lite Mode: Analog: 32*(AHD/TVI/CVI: 1080P/720P; Analog: 960H) Analog+Network: 30*Analog+2*network(Max 8MP), 28*Analog+4*network(Max 8MP), 26*Analog+6*network(Max 8MP), 24*Analog+8*network(Max 8MP), 22*Analog+10*network(Max 8MP), 20*Analog+12*network(Max 8MP), 18*Analog+14*network(Max 8MP), 16*Analog+16*network(Max 8MP), 14*Analog+18*network(Max 8MP), 12*Analog+20*network(Max 8MP), 10*Analog+22*network(Max 8MP), 8*Analog+24*network(Max 8MP), 6*Analog+26*network(Max 8MP), 4*Analog+28*network(Max 8MP), 2*Analog+30*network(Max 8MP) Network: 32*network(Max 8MP)(Total incoming bandwidth ≤160M)	
Input	32CH BNC	
Signal Type	Analog/AHD/CVI/TVI/Network	
Output	1 HD, 1 VGA, 1 CVBS	
Audio		
Input	12 Channel, RCA	
Two-way Audio	NO	
Output	1 Channel, RCA	
Alarm		
Sensor Input	16 Channel	
Output	4 Channel	
Motion Detection	32 Channel	
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)	
Email Alarm	Send Image to The Designated E-mail	
PTZ		
Interface	RS485	
Protocol	Pelco-D, Pelco-P	
Baud Rate	110~921600	
Address	0~255	
Display		
VGA	Resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz	
HD Output	Resolution: 3840×2160/30Hz, 1920 × 1080P /60Hz, 1280 × 1024 /60Hz	
Display Split	36 Channel/25 Channel/16 Channel/9 Channel/8 Channel/4 Channel / 1Channel	

Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.265/H.265+/H.264/H.264+
Audio Compression	G711u
Resolution	5MP(2592×1944),8MP_LITE(1920×2160),5MP_HALF(1296×1944),4MP(2560×1440),4MP_HALF(1280×1440), 3MP(2048×1536),1080P(1920×1080), 720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	worst/worse/ordinary/well/best
Record Rate	Normal Mode: Analog:PAL:8MP_LITE(1920×2160 32*8fps), 5MP(2592×1944 32*6fps), 5MP_LITE(1296×1944 32*10fps), 4MP(2560×1440 32*8fps), 4MP_LITE(1280×1440 32*15fps),3MP(2048×1536 32*9fps),1080P(1920x1080 32*15fps), 720P(1280×720 32*25fps), 960H(960×576 32*25fps) NTSC:8MP_LITE(1920×2160 32*8fps), 5MP(2592×1944 32*6fps),5MP_LITE(1296×1944 32*10fps), 4MP(2560×1440 32*8fps),4MP_LITE(1280×1440 32*15fps),3MP(2048×1536 32*9fps),1080P(1920x1080 32*15fps), 720P(1280×720 32*30fps), 960H(960×480 32*30fps) Lite Mode: Analog: Half 1080P(960x1080 32*25fps),720P(1280×720 32*25fps), 960H(P:960×576 32*25fps/N:960×480 32*30fps) Pure IP(H.265): PAL:4k@17×25fps,5MP@26×25fps,4MP@32x25fps,3MP@32×25fps,1080P@32×25fps, 960P@32×25fps,720P@32×25fps,D1@32×25fps NTSC: 4k@17×30fps,5MP@26×30fps,4MP@32×30fps,3MP@32×30fps,1080P@32×30fps, 960P@32×30fps, 720P@32×30fps, D1@32×30fps
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Decode Capability	9CH 720P@30fps
Sync Playback	Pure Analog: 16CH 8MP_LITE@8fps, 16CH 5M@6fps,16CH 5MP_LITE@10fps, 16CH 4M@8fps, 16CH 4MP_LITE@15fps, 16CH 3M@9fps, 16CH 1080p@15fps, 16CH 1080N@25fps Mix Mode: 2CH 4K@30fps, 2CH 5M@30fps, 2CH 4M@30fps, 3CH 3M@30fps, 8CH 1080P@30fps, 8CH 960P@30fps, 8CH 720P@30fps Pure IPC: 2CH 4K@30fps, 4CH 5M@30fps, 4CH 4M@30fps, 5CH 3M@30fps, 9CH 1080P@30fps, 9CH 960P@30fps, 9CH 720P@30fps
Remote Playback	4 Channel / 1 Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with fomat FAT 32)/Network/FTP
Network	
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1~30fps)
Smart Phone	iPhone, ipad, Android ,Android pad
Hard Disk Driver	
Interface Type	8 SATA Interface
Capacity	8 SATA Hard Disk (3.5" SATA, Up to 64TB) + 1 E-SATA Interface (Up to 8TB)
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa,German, French, Portuguese, Turkic, Spanish, Italian,
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	AC 115~230v ≤35W (Without HDD)
Working Environment	-10~55℃/10~90%
Dimension (W×D×H)	440*450*95(mm)

Weight	9.8kg (Without HDD)
--------	---------------------