

NEOVISION



◆ SPECIFICATION

Model NO.	NBA4KW12		
Video Output Mode	AHD/TVI:8M@15fps,5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI:8M@15fps/12.5fps,4M/2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps	AHD: 8M@15fps, 2M@30fps; TVI/CVI: 8M@15fps/12.5fps, 2M@30fps;

Camera

Image Sensor	1/2.5" CMOS sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	1/1.8" OmniVision CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	8M:3840*2160 2M:1920*1080
Electronic Shutter	AUTO	AUTO	AUTO
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan

Lens

Focus Length	Board Lens 2.8-12mm	Board Lens 2.8-12mm	Board Lens 3.6mm
Focus Control	Manual	Manual	Fixed
Lens Type	Manual	Manual	Fixed

Night Vision

IR Cut Filter	YES	YES	YES
Infrared LED	42μ x6PCS	42μ x6PCS	42μ x6PCS
Infrared Distance	60M	60M	60M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control

Camera Features

Starlight	/	/	/
Day/Night	YES	YES	YES
OSD Menu Language	YES	YES	YES
Noise Reduction	3DNR	3DNR	3DNR
WDR	DWDR	YES	YES
UTC	YES	YES	YES
Noise Reduction	3DNR	3DNR	3DNR

White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO
General			
Housing	IP67	IP67	IP67
Bracket	YES	YES	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,900mA	DC12V±10%,900mA	DC12V±10%,900mA
Dimension	211(W) x 92(H) x 90(D)mm	211(W) x 92(H) x 90(D)mm	211(W) x 92(H) x 90(D)mm
Weight	1.4Kg	1.4Kg	1.4Kg