

**NEOVISION**  
הכי קרוב למציאות!



## SPECIFICATION

Model NO. NBPOEFC8MP

### Camera

Image Sensor 1/2.8" SONY Starvis Back-illuminated CMOS sensor

Resolution 8MP

Effective Pixels 3864(H)\*2192(V)

Compression H.264/H.265/JPEG/AVI

Audio Compression G711A/U,AAC

TV System PAL/NTSC

Electronic Shutter Time Auto: 1/3-1/1000000Sec

Minimum Illumination Color : 0.02 lux@F1.6, 0 Lux with white light

S/N Ratio  $\geq 52$ dB

Scanning System Progressive

Video Output Network

Reset Button Optional

### Lens

Focus Length 3.6mm

Focus Control Fixed

Lens Type Fixed

Pixels 8MP

### Night Vision

Infrared LED No,Support Warm light LED 4000K, up to 25m

Infrared Distance	N/A
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, SNMP
ONVIF	Support ONVIF 19.12(Profile S/T/G)
P2P	YES
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160@18fps
Main Stream 2	2560*1440@18fps
Main Stream 3	1920*1080@18fps 1280*720@18fps
Sub Stream 1	1280*720@18fps
Sub Stream 2	720*480@18fps
Sub Stream 3	N/A
Tri Stream	N/A
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, Android
<b>AI Function</b>	
Intelligent Analysis	Intrusion Detetion, Line Cross Detetion, Loiter Detetion People Gather Detecion(based on human detection), Motion detection based on human detection
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Image Config	White Balance, FLK(Flicker Control),Occlusion Detection,HLC Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR
Full Color	Support
Corridor Pattern	Support
Defog Mode	N/A

ROI	Support
BLC	Support
WDR	120dB
Motion Detection	Support(support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Turkish, Spanish, Hebrew, Italian, Nederland, Czech, Vietnamese Arabic, German, Russian, French, Korean, Portuguese, Japanese

### Interface

Audio	Optional 1 Built-in MIC
Alarm	N/A
SD Card Slot	Optional Internal, Support Max 512GB
RS485	N/A

### General

Housing	Metal ,IP67
Anti-cut Bracket	No
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	70(W) x 67.5(H) x 169(L)mm
Weight	600g